PILOT CHEMICAL COMPANY

We're going further®

www.pilotchemical.com
9075 Centre Pointe Drive • Suite 400
West Chester, OH 45069

MASON® CS-24M

PRODUCT DATA SHEET

PDS 872101(2).ACTIVE06142023

PRODUCT DESCRIPTION

Mason® CS-24M is an 80% active blend of alkyl dimethyl benzyl ammonium chloride, ADBAC, and didecyl dimethyl ammonium chloride, DDAC, compounds in a water and ethanol solution. Mason® CS-24M is a versatile cationic surfactant that can be used in a wide range of applications.

COMMON CHEMICAL NAME

Alkyl dimethyl benzyl ammonium chloride, Didecyl dimethyl ammonium chloride, Octyl decyl dimethyl ammonium chloride, Dioctyl dimethyl ammonium chloride

CAS #

68424-85-1, 7173-51-5, 32426-11-2, 5538-94-3

TYPICAL PROPERTIES

Appearance at 25°C	Clear, colorless to light straw liquid
Active (MW: 342), wt. %	80.0
Free Amine + Free Amine HCl, wt. %	< 4.0
Ethanol, wt.%	9 - 15
pH (10% Solution)	6.0 – 9.0
Color (as is), APHA	< 200
Freeze Point	-20ºC (-4ºF)
Shelf life	2 years

APPLICATIONS

Mason® CS-24M is a cationic surfactant that can be used in various products including HI&I deodorizers and cleaners, oil and gas applications and personal care formulations. Mason® CS-24M can be used an emulsifier in degreasers, pine oil and d-Limonene cleaners, and an anti-stat in vehicle cleaners. Mason® CS-24M can be used as a deodorizer to remediate mildew odor in textiles, and as a general odor control agent in formulated sanitation products. Mason® CS-24M can be used as antistatic and hair conditioning agent in personal care cleansing formulations.

ADVANTAGES

The high purity of the starting material delivers a consistent, low color and odor, high performance product that can be differentiated into consistent, high value end-use products.

HANDLING & STORAGE

Refer to the Mason® CS-24M SDS (Safety Data Sheet) before handling. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment and observe good industrial hygiene practices. Material is slippery on wet and hard surfaces. Store in tightly closed container. Do not store with strong oxidizing agents. Avoid excessive heat. Recommended storage temperatures above 35°F. Product is not damaged by freezing. If material becomes frozen it should be heated gently and stirred to ensure it is homogeneous before use.

PACKAGING

Mason® CS-24M is available in 410 lb. poly. drum and 2000 lb. poly. totes.

See starting formulas and additional product information at www.pilotchemical.com.

The information and suggestions given are drawn from data we believe to be reliable, but in all cases, the user should check and confim the suggestions and results in his own use before proceeding further. None of the suggestions or recommendations constitute freedom from any patents that may be existent in the field or be issued.

RESPONSIBLE CARE® OUR COMMITMENT TO SUSTAINABILITY